

Specifications

	MODEL 8000 CRANE SCALE	MODEL 8100 TENSION LINK
Capacity	1 ton, 2 ton, 5 ton, 8 ton	10 ton, 20 ton, 50 ton
Tare Weight Range F.S.	100 %	100 %
Safe Overload Capacity	150 % (500 % Ultimate)	200 % (500 % Ultimate)
Overload Indication	Yes	Yes
Calibration	Precalibrated	Precalibrated
Resolution	1 ton 2,000 x 1 lb 2 ton 4,000 x 2 lb 5 ton 10,000 x 2 lb 8 ton 16,000 x 5 lb	10 ton 10 x 0.01 ton 20 ton 20 x 0.01 ton 50 ton 50 x 0.01 ton
Displayed Units	Pounds (lb)	Tons (t)
Applied Load Accuracy	0.1 %	0.15 %
Temperature	14 °F to 122 °F (-10 °C to 50 °C)	14 °F to 122 °F (-10 °C to 50 °C)
Batteries	2 Rechargeable NiCad Batteries 1.2 V, 7000 mAh capacity	2 Rechargeable NiCad Batteries 1.2 V, 7000 mAh capacity
Battery Life	200 Hour Continuous Use (120 Hour in RF Remote Mode)	200 Hour Continuous Use (120 Hour in RF Remote Mode)
Battery Charger	3 V, 700 mA	3 V, 700 mA
Low Battery Indicator	Yes	Yes
Automatic Power Off	Yes	Yes
Housing/Material	IP54 Cast Aluminum Enclosure	IP54 Machined Aluminum Enclosure
Warranty	2 Year Limited	2 Year Limited
Display	0.8", 5 Digit LCD	0.8", 5 Digit LCD
Display Update Rate	0.5 sec	0.5 sec
Non-Linearity	0.1 % F.S.	0.15 % F.S.
Hysteresis	0.1 % F.S.	0.15 % F.S.
Non-Repeatability	0.1 % F.S.	0.15 % F.S.
Connect to Printer or PC	Yes	Yes
RF Control Capability	Preprogrammed for remote control	Preprogrammed for remote control
Additional Remote Control(s) Capability	Add on 1 or more Remote Control(s) with same ID # (RF models only)	Add on 1 or more Remote Control(s) with same ID # (RF models only)
Accessories Included	Molded Carrying Case	Molded Carrying Case
Usage	Indoor Use	Indoor Use
Other Features...	Software for data transmission to PC 180° Load Cell Rotation	Software for data transmission to PC Use to test tension cables Can be used as a crane scale
Options	Crosby Hardware	Crosby Hardware

Your local Distributor is:



42860 Nine Mile Road
Novi, MI 48375-4122
Phone: 248-596-0600
Fax: 248-596-0601
Toll Free: 800-755-7875
www.gse-inc.com

Lüripper Straße 62
41065 Monchengladbach Germany
Phone: 0049 (0) 2161-59906-11
Fax: 0049 (0) 2161-59906-20
www.gse-europe.de

